

Cushion Hanger Kit, for 2x65 series wave guide cable

- Manufactured by EPDM & stainless steel
- Excellent for outdoor use
- Universal fixing design on wall, pole, angle steel



Part Number-StatusActiveDetail DescriptionCushion hanger kit, for 2×(φ30mm-φ51mm) cableGeneral SpecificationsEVDM rubber & SS304MaterialEPDM rubber & SS304Cable typeElliptical WaveguideCable size2 cables Waveguide Cable Series 65ColorBlackDimensions24.5 mm 0.96 inLength24.5 mm 0.96 inLength32 mm 3.27 inNominal size2×(φ30mm-φ51mm)UV resistance>1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width220 mm 8.66 inBag lengthCamp head & Hose clamp & Cushion insertIncludedClamp head & Hose clamp & Cushion insert	Product Classification	
StatusActiveDetail DescriptionCushion hanger kit. for 2×(φ30mm-φ51mm) cableGeneral SpecificationsEPDM rubber & SS304MaterialEPDM rubber & SS304Cable typeCliptical WaveguideCable size2 cables Waveguide Cable Series 65ColorBlackDimensionsEHeight24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental Specifications2×(φ30mm-φ51mm)UV resistance>1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertRescaging quantity and UOMKit of 5	Material Code	6004965
Detail DescriptionCushion hanger kit. for 2×(φ30mm-φ51mm) cableGeneral SpecificationsEPDM rubber & SS304MaterialEPDM rubber & SS304Cable typeElliptical WaveguideCable size2 cables Waveguide Cable Series 65ColorBlackDimensionsImage: Stand	Part Number	-
General Specifications Material EPDM rubber & SS304 Cable type Elliptical Waveguide Cable size 2 cables Waveguide Cable Series 65 Color Black Dimensions 24.5 mm 0.96 in Length 24.5 mm 0.96 in Nominal size 2×(φ30mm-φ51mm) Environmental Specifications 2×(q30mm-φ51mm) UV resistance >1000Hours,based on ISO 4892-3 Packaging and Weights 220 mm 8.66 in Bag width 320 mm 12.6 in Included Clamp head & Hose clamp & Cushion insert Packaging quantity and UOM Kit of 5	Status	Active
MaterialEPDM rubber & SS304Cable typeElliptical WaveguideCable size2 cables Waveguide Cable Series 65ColorBlackDimensionsHeightLength24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental SpecificationsUV resistance≥1000Hours,based on ISO 4892-3Packaging and WeightsBag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOM	Detail Description	Cushion hanger kit, for $2 \times (\varphi 30 \text{mm} - \varphi 51 \text{mm})$ cable
Cable typeElliptical WaveguideCable size2 cables Waveguide Cable Series 65ColorBlackDimensions24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental Specifications2100Hours,based on ISO 4892-3VY resistance≥1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	General Specifications	
Cable size2 cables Waveguide Cable Series 65ColorBlackDimensionsHeight24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental SpecificationsUV resistance≥1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width220 mm 12.6 inBag lengthClamp head & Hose clamp & Cushion insertIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Material	EPDM rubber & SS304
ColorBlackDimensionsHeight24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental SpecificationsUV resistance≥1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width220 mm 12.6 inBag lengthClamp head & Hose clamp & Cushion insertIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Cable type	Elliptical Waveguide
DimensionsHeight24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental Specifications≥1000Hours,based on ISO 4892-3UV resistance≥1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Cable size	2 cables Waveguide Cable Series 65
Height24.5 mm 0.96 inLength83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental SpecificationsUV resistance≥1000Hours,based on ISO 4892-3Packaging and WeightsBag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Color	Black
Length83 mm 3.27 inNominal size2×(φ30mm-φ51mm)Environmental Specifications≥1000Hours,based on ISO 4892-3UV resistance≥1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Dimensions	
Nominal size2×(φ30mm-φ51mm)Environmental Specifications≥1000Hours,based on ISO 4892-3UV resistance≥1000Hours,based on ISO 4892-3Packaging and Weights220 mm 8.66 inBag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Height	24.5 mm 0.96 in
Environmental Specifications UV resistance ≥1000Hours,based on ISO 4892-3 Packaging and Weights Bag width 220 mm 8.66 in Bag length 320 mm 12.6 in Included Clamp head & Hose clamp & Cushion insert Packaging quantity and UOM Kit of 5	Length	83 mm 3.27 in
UV resistance ≥1000Hours,based on ISO 4892-3 Packaging and Weights 220 mm 8.66 in Bag width 220 mm 8.66 in Bag length 320 mm 12.6 in Included Clamp head & Hose clamp & Cushion insert Packaging quantity and UOM Kit of 5	Nominal size	2×(φ30mm-φ51mm)
Packaging and WeightsBag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Environmental Specifications	
Bag width220 mm 8.66 inBag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	UV resistance	≥1000Hours,based on ISO 4892-3
Bag length320 mm 12.6 inIncludedClamp head & Hose clamp & Cushion insertPackaging quantity and UOMKit of 5	Packaging and Weights	
Included Clamp head & Hose clamp & Cushion insert Packaging quantity and UOM Kit of 5	Bag width	220 mm 8.66 in
Packaging quantity and UOM Kit of 5	Bag length	320 mm 12.6 in
	Included	Clamp head & Hose clamp & Cushion insert
Weight, gross 0.665 kg 1.47 lb	Packaging quantity and UOM	Kit of 5
	Weight, gross	0.665 kg 1.47 lb

For more information, please visit: www.maxdao.com ©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Feb 22, 2023 Public





Certifications and Compliance

ISO 9001:2015

ROHS

Designed, manufactured and/or distributed under this quality management system

Compliant

For more information, please visit: www.maxdao.com

(in

©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Feb 22, 2023 Public



Page 2 of 2