

## Cold Shrink Tube,φ45×130mm

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



### Product Classification

Material Number	6002899
Part Number	-
Status	Active
Detail description	Cold shrink tube,φ45×130mm

### General Specifications

Material	Silicone rubber
Cable type	Corrugated   Elliptical Waveguide   Smoothwall
Cable size	φ20mm-φ40mm
Color	Black
Mastic(Y/N)	Y
Shrink ratio	2:1

### Dimensions

Length before shrink	130 mm   5.12 in
Length after shrink	250 mm   9.84 in
Inner diameter before shrink(ID)	45 mm   1.77 in
Inner diameter after shrink(ID)	17 mm   0.67 in
Thickness after shrink	2.3 mm   0.09 in

### Environmental Specifications

Operating temperature	-40°C to +85°C (-40°F to +185°F)
Weatherproof resistance	IP67,based on ISO20653:2013
UV resistance	≥720Hours,based on ISO 4892-3

### Packaging and Weights

Bag width	300 mm   10.24 in
Bag length	450 mm   12.6 in
Packaging quantity and UOM	1 pcs

For more information, please visit:  
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised:Mar 9, 2023

Public

Weight gross

0.104 kg | 0.229 lb

---

**Certifications and Compliance**

---

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

ROHS

Compliant

