

Jumper cable, 3/8" superflexible cable, DIN male to DIN male right, 6 meter

- Stable premium VSWR, outstanding and consistent intermodulation performance
- Improves network performance, reduces the number of dropped calls and avoids revenue loss
- RoHS certified



Product Classification	
Material Code	6000973
Part Number	-
Status	Active
Detail Description	Jumper cable, 3/8" superflexible cable, 7/16 DIN male to 7/16 DIN male right angle, 6 meter
General Specifications	
Connector 1 Type	7/16 DIN male
Connector 2 Type	7/16 DIN male right angle
Cable Type	3/8" Superflexible Cable
Dimensions	
Length	6 Meter
Electrical Specifications	
Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤1.15(DC-3GHz)
PIM3	≤-160dBc
Mating Cycles	≥500
Environmental Specifications	
Installation Temperature	-25 °C to +60 °C
Operating Temperature	-40 °C to +85 °C
Waterproof	IEC 60529, IP68
Packaging and Weights	
Height, packed	60 mm 2.36 in
Width, packed	300 mm 11.81 in
	200
Length, packed	300 mm 11.81 in

DOC#ITM-04-01, Version:A/2, Updated:02/25/2023





Weight, gross	1.44 kg 3.17 lb
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant