

Fiber Optic Attenuator, single mode LC/UPC male to female, blue

- Designed to reduce or balance the power in passive optical networks
- Insert-able between the connector and the adapter and therefore suited for distribution frames, cabinets and boxes
- High system flexibility because of wave-length independency and polarization insensitivity
- RoHS certified



Product Classification

Material Code	6004486
Part Number	-
Status	Active
Detail Description	Fiber Optic Attenuator, single mode LC/UPC male to female, 5dB, blue

General Specifications

Color	Blue
Connector 1 Type	LC/UPC male
Connector 2 Type	LC/UPC female
Fiber Type	Single mode

Dimensions

Length	25.3 mm
Width	6.1 mm
Height	9.6 mm

Electrical Specifications

Operation Wavelength	1310/1550 nm
Attenuation Value	5 dB
Return Loss	≥ 55 dB

Environmental Specifications

Operating Temperature	-40 °C to +85 °C
-----------------------	------------------

Packaging and Weights

Height, packed	40 mm 1.57 in
Width, packed	40 mm 1.57 in
Length, packed	40 mm 1.57 in
Packaging Quantity and UOM	1 Pcs

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 2, 2023

Public

Weight, gross

0.002 kg | 0.004 lb

Certifications and Compliance

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

