

RF Attenuator, SMA male to SMA female

- Excellent low PIM performance
- RoHS certified



Product Classification

Material Code	6006563
Part Number	-
Status	Active
Detail Description	RF Attenuator, SMA male to SMA female

General Specifications

Material	Stainless steel 304
Surface Treatment	Passivation
Connector 1 Type	SMA male
Connector 2 Type	SMA female

Dimensions

Length	25 mm
Outer Diameter	Φ7 mm

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-18GHz
VSWR	≤ 1.3
Attenuation Value	1-30 dB
Power	1 W

Environmental Specifications

Operating Temperature	-55 °C to +125 °C
-----------------------	-------------------

Packaging and Weights

Height, packed	40 mm 1.57 in
Width, packed	40 mm 1.57 in
Length, packed	40 mm 1.57 in

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 6, 2023

Public

Packaging Quantity and UOM	1 Pcs
Weight, gross	0.008 kg 0.017 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

