# Copper Lug, AWG 3/0#, four hole 1/4", hole spacing 5/8", standard barrel, with inspection window


- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars.
- Copper Tube Terminals between 6mm<sup>2</sup> & 800mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.



ΜΑΧΡΔΟ

Product Classification	
Material Code	6004852
Part Number	-
Detail Description	Copper Lug, AWG 3/0#, four hole 1/4", hole spacing 5/8", standard barrel, with inspection window
General Specifications	
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Finish	Tin-plated
Inspection Window	With inspection window

## **Dimensions**



Bolt Size	1/4 in   7.0 mm
Hole Spacing (H)	5/8 in   16.0 mm
Tang Width (C)	1.38 in   35.0 mm
Barrel length (B)	1.00 in   25.4 mm
Overall length (L)	3.24 in   82.5 mm
Inner diameter (d)	0.51 in   13.0 mm
Outer diameter (D)	0.70 in   16.9 mm

### **Electrical Specifications**

Rating - Maximum Voltage 35KV

## **Environmental Specifications**

**Operating Temperature** For more information, please visit:

-40 °C to +90°C (-40 °F to +212 °F)





TEMPLATE# ITM-04-01 VERSION A/3 DATE 03/04/2023

www.maxdao.com



Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.158 lb   0.072 kg
Certifications and Certificated	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant



www.maxdao.com