

Jumper cable, 1/2" superflexible cable, DIN male to DIN female, 6 meter

- Stable premium VSWR, outstanding and consistent intermodulation performance
- Improves network performance, reduces the number of dropped calls and avoids revenue loss
- RoHS certified

**Product Classification**

Material Code	6001592
Part Number	-
Status	Active
Detail Description	Jumper cable, 1/2" superflexible cable, 7/16 DIN male to 7/16 DIN female, 6 meter

General Specifications

Connector 1 Type	7/16 DIN male
Connector 2 Type	7/16 DIN female
Cable Type	1/2" Superflexible Cable

Dimensions

Length	6 Meter
--------	---------

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤1.15(DC-3GHz)
PIM3	≤-160dBc
Mating Cycles	≥500

Environmental Specifications

Installation Temperature	-25 °C to +60 °C
Operating Temperature	-40 °C to +85 °C
Waterproof	IEC 60529, IP68

Packaging and Weights

Height, packed	300 mm 11.81 in
Width, packed	300 mm 11.81 in
Length, packed	100 mm 3.93 in



Packaging Quantity and UOM	1 Pcs
Weight, gross	1.62 kg 3.63 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

