

**Jumper cable, 3/8" superflexible cable, DIN male right to DIN male right, 3 meter**

- **Stable premium VSWR, outstanding and consistent intermodulation performance**
- **Improves network performance, reduces the number of dropped calls and avoids revenue loss**
- **RoHS certified**

**Product Classification**

Material Code	6000940
Part Number	-
Status	Active
Detail Description	Jumper cable, 3/8" superflexible cable, 7/16 DIN male right to 7/16 DIN male right angle, 3 meter

**General Specifications**

Connector 1 Type	7/16 DIN male
Connector 2 Type	7/16 DIN male right angle
Cable Type	3/8" Superflexible Cable

**Dimensions**

Length	3 Meter
--------	---------

**Electrical Specifications**

Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤1.15(DC-3GHz)
PIM3	≤-160dBc
Mating Cycles	≥500

**Environmental Specifications**

Installation Temperature	-25 °C to +60 °C
Operating Temperature	-40 °C to +85 °C
Waterproof	IEC 60529, IP68

**Packaging and Weights**

Height, packed	60 mm   2.36 in
Width, packed	300 mm   11.81 in
Length, packed	300 mm   11.81 in

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 25, 2023  
 Public

Packaging Quantity and UOM	1 Pcs
Weight, gross	0.72 kg   1.58 lb

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

