01 VERSION A/4 DATE 03/25/2023



Waveguide clamp ,for R100 waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 ℃
- RoHS certified



Product Classification	
Material Number	6000937
Part Number	-
Status	Active
Detail Description	Waveguide cable clamp, for R100 waveguide
General Specifications	
Metal Parts Material	Stainless steel 304
Rubber Parts Material	EPDM
Mounting Plate Thickness	3-25mm
Dimensions	
Threaded Rod Length	400 mm 15.75 in
Adapter Width	24 mm 0.94 in
Rubber Lining Hole	31 mm X 17 mm
Waveguide Size	R100 WR90 WG16
Environmental Specifications	
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	ASTM G155, 720 hours
Salt Spray	ASTM B117, 72 hours
Packaging and Weights	
Width, packed	600 mm 23.62 in
Length, packed	150 mm 5.91in
Included	Angle adapter M8 spring washer M8 nut M8 threaded rod Rubber lining Clamp
UOM	Pcs
Packaging	Вад

For more information, please visit: www.maxdao.com



Page 1 of 2







Weight, gross 0.332 kg | 0.732 lb **Certifications and Compliance** Designed, manufactured and/or distributed under this ISO 9001:2015 quality management system RoHS Compliant

