MAXDAO

Waveguide clamp ,for R120 waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 ℃
- **RoHS** certified



Product Classification	
Material Number	6001267
Part Number	-
Status	Active
Detail Description	Waveguide cable clamp, for R120 waveguide
General Specifications	
Metal Parts Material	Stainless steel 304
Rubber Parts Material	EPDM
Mounting Plate Thickness	3-25mm
Dimensions	
Threaded Rod Length	400 mm 15.75 in
Adapter Width	24 mm 0.94 in
Rubber Lining Hole	28 mm X 19 mm
Waveguide Size	R120 WR75 WG17
Environmental Specifications	
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	ASTM G155, 720 hours
Salt Spray	ASTM B117, 72 hours
Packaging and Weights	
Width, packed	600 mm 23.62 in
Length, packed	150 mm 5.91 in
Included	Angle adapter M8 spring washer M8 nut M8 threaded rod Rubber lining Clamp
UOM	Pcs
Packaging	Bag

For more information, please visit: www.maxdao.com







©Copyright 2023 Maxdao Inc. All rights reserved.



Weight, gross 0.341 kg | 0.752 lb **Certifications and Compliance** Designed, manufactured and/or distributed under this ISO 9001:2015 quality management system RoHS Compliant



www.maxdao.com

For more information, please visit: