## r

## Waveguide clamp ,for R140 waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 ℃
- RoHS certified



**MAXDAO** 

Product Classification	
Material Number	6001258
Part Number	-
Status	Active
Detail Description	Waveguide cable clamp, for R140 waveguide
General Specifications	
Metal Parts Material	Stainless steel 304
Rubber Parts Material	EPDM
Mounting Plate Thickness	3-25mm
Dimensions	
Threaded Rod Length	400 mm   15.75 in
Adapter Width	24 mm   0.94 in
Rubber Lining Hole	25 mm X 15 mm
Waveguide Size	R140   WR62   WG18
Environmental Specifications	
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	ASTM G155, 720 hours
Salt Spray	ASTM B117, 72 hours
Packaging and Weights	
Width, packed	600 mm   23.62 in
Length, packed	150 mm   5.91in
Included	Angle adapter   M8 spring washer   M8 nut   M8 threaded rod   Rubber lining   Clamp
UOM	Pcs
Packaging	Bag

For more information, please visit: www.maxdao.com

©Copyright 2023 Maxdao Inc. All rights reserved.

Page 1 of 2







Weight, gross 0.367 kg | 0.809 lb **Certifications and Compliance** Designed, manufactured and/or distributed under this ISO 9001:2015 quality management system RoHS Compliant

