Waveguide clamp ,for R220 waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 °C
- RoHS certified



ΜΑΧΟΔΟ

Product Classification	
Part Number	-
Status	Active
Detail Description	Waveguide cable clamp, for R220 waveguide
General Specifications	
Metal Parts Material	Stainless steel 304
Rubber Parts Material	EPDM
Mounting Plate Thickness	3-25mm
Dimensions	
Threaded Rod Length	400 mm 15.75 in
Adapter Width	24 mm 0.94 in
Rubber Lining Hole	19 mm X 12 mm
Waveguide Size	R220 WR42 WG20
Environmental Specifications	
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	ASTM G155, 720 hours
Salt Spray	ASTM B117, 72 hours
Packaging and Weights	
Width, packed	600 mm 23.62 in
Length, packed	150 mm 5.91 in
Included	Angle adapter M8 spring washer M8 nut M8 threaded rod Rubber lining Clamp
UOM	Pcs
Packaging	Bag

For more information, please visit: www.maxdao.com ©Copyright 2023 Maxdao Inc. All rights reserved.

Public

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Apr 4, 2023 Page 1 of 2



DATASHEET

Weight, gross

Certifications and Compliance

ISO 9001:2015

RoHS

0.356 kg | 0.785 lb

Designed, manufactured and/or distributed under this quality management system Compliant



©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Apr 4, 2023 Public

Page 2 of 2

MAXDAO