Hoisting Grip, Pre-Laced, for 0.75-0.83 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.

Revised: May 11, 2023

Public

• CE certified

 \boxtimes

fin



Product Classification	
Material Number	6004883
Part Number	-
Status	Active
Detail Description	Hoisting Grip, Pre-Laced, for 0.75-0.83 in Cable
Details	
Cable Range	0.75-0.83 in 19.0-21.0 mm
Mesh Length	10.0 in 254.0 mm
Eye Length	12.0 in 304.8 mm
Approximate Break Streng	gth 2400 lbs 1088.6 kg
Working Load	480 lbs 218.0 kg (Safety Factor 5*)
Maximum Spacing Interva	als 200 ft 60.96 m
Mesh Material	Stainless Steel
Support Clamp	Included
Warning Label	Yellow Mylar
Packaging and Weights	
UOM	1 pcs
Packaging	Bag
Weight, gross	0.22 lb 0.1 kg
Certifications and Comp	liance
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant
For more information, please visit: www.maxdao.com	©Copyright 2023 Maxdao Inc. All rights reserved. Page 1 of 4 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.