


Hybrid Junction Box, for Fiber & Power Connections

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on wall, pole, angle steel
- IP 67 Waterproof
- UV Resistant
- RoHS certified



Product Classification

Detail Description	Hybrid Junction Box, for Fiber & Power Connections
--------------------	--

General Specifications

Box Material	High- impact polycarbonate, UV resistant
Box Color	Light grey
DC Connections	DIN Rail Terminals, UL Listed
Fibre Connections	LC Adapter
Mounting	Mounted On Pole, Wall, Ladder

Dimensions

Width	330 mm (with door)
Height	280 mm (with door)
Depth	170 mm (with door)

Environmental Specifications

Operating Temperature	-40 °C to +80 °C
Installation Temperature	-20 °C to +60 °C
Weatherproofing Method	IEC 60529:2001, IP67
UV Resistant	ASTM G155, 1000 hours
Salt Spray (Outer)	IEC 60502-4, 720 hours

Packaging and Weights

Included	Mounting kit
Packaging Quantity and UOM	1 Kit
Weight, gross	2.27 kg 5 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant