

Universal Grounding Kit ,for cable 1/2"-3", 1.5 m

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for 1/2"-3" coaxial cable
- Operation Temperature -40°C~70 °C
- Waterproof IP67



Product Classification

Item Number	6001481
Part Number	-
Status	Active
Detail Description	Universal Grounding Kit,for cable 1/2"-3", 1.5m, installation accessories including

General Specifications

Bonding Conductor Jacket Material	PVC
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG6
Cable Color	Black
Grounding Strap Material	Copper
Lug Type	Two-hole lug

Dimensions

Bonding Conductor Length	1.5 mm 60 in
Suitable Cable	1/2"-3"
Lug Hole Size	3/8 in
Screw Size	3/8"x1"

Electrical Specifications

Contact Transition Resistance	≤ 10mΩ
Lightning Current Carrying Capability	25 KA

Environmental Specifications

Operating Temperature	-40 °C to +70 °C
Storage Temperature	-40 °C to +70 °C
Weatherproofing Method	Butyl and electric tape

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 16, 2023
 Public

Packaging and Weights

Height, packed	370 mm 14.56 in
Width, packed	210 mm 8.26 in
Included	Grounding kit Hardware Lug One roll of PVC tape One roll of rubber tape
UOM	Kit
Packaging	Bag
Weight, gross	0.60 kg 1.32 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

