

**Tinned Universal Grounding Kit ,for cable 1/2"-3",1.5 m**

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for 1/2"-3" coaxial cable
- Operation Temperature -40°C~70 °C
- Waterproof IP67

**Product Classification**

|                    |  |
|--------------------|--|
| Item Number        | 6001995  |
| Part Number        | -  |
| Status             | Active   |
| Detail Description | Tinned Universal Grounding Kit,for cable 1/2"-3", 1.5m, installation accessories including |

**General Specifications**

|                                   |               |
|-----------------------------------|---------------|
| Bonding Conductor Jacket Material | PVC           |
| Bonding Conductor Material        | Copper        |
| Bonding Conductor Wire Size       | AWG6          |
| Cable Color                       | Black         |
| Grounding Strap Material          | Tinned Copper |
| Lug Type                          | Two-hole lug  |

**Dimensions**

|                          |                |
|--------------------------|----------------|
| Bonding Conductor Length | 1.5 mm   60 in |
| Suitable Cable           | 1/2"-3"        |
| Lug Hole Size            | 3/8 in         |
| Screw Size               | 3/8"x1"        |

**Electrical Specifications**

|                                       |        |
|---------------------------------------|--------|
| Contact Transition Resistance         | ≤ 10mΩ |
| Lightning Current Carrying Capability | 25 KA  |

**Environmental Specifications**

|                        |                         |
|------------------------|-------------------------|
| Operating Temperature  | -40 °C to +70 °C        |
| Storage Temperature    | -40 °C to +70 °C        |
| Weatherproofing Method | Butyl and electric tape |

For more information, please visit:  
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 16, 2023

Public

---

**Packaging and Weights**

---

|                |  |
|----------------|--|
| Height, packed | 370 mm   14.56 in  |
| Width, packed  | 210 mm   8.26 in   |
| Included       | Grounding kit   Hardware   Lug   One roll of PVC tape  <br>One roll of rubber tape |
| UOM            | Kit  |
| Packaging      | Bag  |
| Weight, gross  | 0.60 kg   1.32 lb  |

---

**Certifications and Compliance**

---

|               |   |
|---------------|---|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this<br>quality management system |
| RoHS          | Compliant   |

