

GST Grounding Kit ,for LMR400 cable,1.5 m

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for LMR400 cable
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification

Material Number	6006276
Status	Active
Detail Description	GST Grounding Kit,for LMR400 cable,1.5m,installation accessories including

General Specifications

Bonding Conductor Material	Copper, Tin Plated
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper, Tin Plated
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl

Dimensions

Bonding Conductor Length	1.5m 59.1 in
Lug Hole Size	3/8"
Screw Size	3/8"x1"

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

Height, packed	180 mm 7.0 in
Width, packed	310 mm 12.2 in

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 23, 2023
 Public

Length, packed	400 mm 15.75 in
Included	Grounding kit 3/8"x1" screw 3/8" spring washer 3/8" flat washer 3/8" nut One roll of 6m PVC tape One roll of 0.6m butyl rubber Tape
UOM	1 Kit
Packaging	Bag
Weight, gross	0.504 kg 1.111 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

