


**Downlead clamp for 0.375"-0.468" OD ADSS Cable**

- Compressive elastomer material protects cable jacket
- Two grooves to support each ADSS downlead
- Mounted to wood pole

**Product Classification**

Item Number	6008400
Part Number	-
Status	Active
Detail Description	Downlead clamp for 0.375"-0.468" OD ADSS Cable

**General Specifications**

Body Material	Urethane
Hardware Material	Galvanized Steel
Applied ADSS Cable OD Range	0.375-0.468 in   10.0-11.8 mm

**Dimensions**

Length	69.9 mm   2.75 in
Width	76.2 mm   3.00 in
Lag Screw	1/2"x4"
Flat Washer	1/2"
Square Washer	2"x2"

**Environmental Specifications**

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	≥48 hours, base on ISO4892.3-1994

**Packaging and Weights**

Height, Packed	200 mm   7.87 in
Width, Packed	200 mm   7.87 in
Included	Installation accessories
UOM	Kit
Packaging	Carton
Weight, Gross	0.41 kg   0.09 lbs



---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

---

