

## AISG RET cable assembly, male to female right angle, 1 m

- Feeds data and power to RET system components
- **RoHS** certified



| Product Classification          |  |  |
|---------------------------------|--|--|
| Material Number                 | 6005645  |  |
| Part Number                     | -  |  |
| Status                          | Active   |  |
| Detail Description              | AISG RET cable assembly, male to female right angle, 8 pin,<br>1 m |  |
| General Specifications          |  |  |
| Body Material                   | Brass Hpb59  |  |
| Body Surface Treatment          | Nickel plating   |  |
| Insulator Material              | PTFE   |  |
| Conductor PIN Material          | Phosphor bronze  |  |
| Conductor PIN Surface Treatment | Ag plating   |  |
| Connector 1 Type                | 8 pin DIN male   |  |
| Connector 2 Type                | 8 pin DIN female right angle                                       |  |
| Date Conductor Type             | 24AWG twisted pair   |  |
| Power Conductor Type            | 20AWG stranded   |  |
| Cable Jacket Material           | PVC  |  |
| Cable Color                     | Black  |  |
| Dimensions                      |  |  |
| Jacket Diameter                 | 7.8 mm   |  |
| Cable Length                    | 1 M  |  |
| Electrical Specifications       |  |  |
| Rated Current                   | 5 A  |  |
| Rated Voltage                   | 300 V  |  |
| Contact Resistance              | ≤ 5 mΩ   |  |
| Dielectric Resistance           | ≥ 5000 MΩ  |  |
| Endurance Cycles                | 500  |  |

For more information, please visit: www.maxdao.com



Page 1 of 2







| Environmental Specifications  |  |
|-------------------------------|--|
| Operating Temperature         | -40 °C to +70 °C   |
| Waterproof                    | IEC 60529, IP67  |
| Packaging and Weights         |  |
| Height, packed                | 50 mm   1.96 in  |
| Width, packed                 | 190 mm   7.48 in   |
| Length, packed                | 190 mm   7.48 in   |
| Packaging Quantity and UOM    | 1 Pcs  |
| Weight, gross                 | 0.3 kg   0.66 lb   |
| Certifications and Compliance |  |
| ISO 9001:2015                 | Designed, manufactured and/or distributed under this quality management system |
| RoHS                          | Compliant  |



www.maxdao.com

For more information, please visit: