TEMPLATE# ITM-04-01 VERSION A/4 DATE 03/25/2023




Acetal double locking head

- **Used with acetal banding**
- **Excellent weather resistance**



| Product Classification | |
|-------------------------------|--|
| Material Number | 6002822 |
| Part Number | - |
| Status | Active |
| Detail Description | Acetal double locking head |
| General Specifications | |
| Body Material | Weather-Resistant Acetel |
| ocking Brab Material | Stainless steel 304 |
| Color | Black |
| Dimensions | |
| Height | 12.5 mm 0.492 in |
| Width | 18.5 mm 0.728 in |
| Length | 21.5 m 0.846 in |
| Mechanical Specifications | |
| Min. Tensile Strength | 1112 N 250 lbs |
| Environmental Specifications | |
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| JV Resistance | ASTM G155, 1000 hours |
| Flammability | UL94 HB |
| Packaging and Weights | |
| Nidth, packed | 200 mm 7.87 in |
| Length, packed | 140 mm 5.51 in |
| JOM | Kit of 25 |
| Packaging | Bag |
| Weight, gross | 0.091 kg 0.201 lb |
| Certifications and Compliance | |
| SO 9001:2015 | Designed, manufactured and/or distributed under this |

For more information, please visit: www.maxdao.com









quality management system

RoHS Compliant



www.maxdao.com

For more information, please visit: