MAXDAO

Support Grips, Bus Drop, Locking Bale Closed Mesh, Galvanized Steel, Cable Range 0.30-0.43"

- Provide support for flexible cord or bus drop cable at bus duct
- Used for absorb additional strain from vibration, expansion, contraction and flexing
- Locking bale attachment fits around beam or pipe and can be locked in place
- Galvanized steel wire mesh is for indoor use only
- UL&CSA, CE certified



Classification	
Material Number	6003304
Part Number	-
Status	Active
Detail Description	Support grips, bus drop, locking bale closed mesh, galvanized steel, cable range 0.30-0.43"
Details	
Cable Range	0.30-0.43 in 7.62-10.92 mm
Mesh Length	4.5 in 114.3 mm
Bale Length	12.0 in 304.8 mm
Approx. Break Strength	1100 lbs 499.0 kg
Working Load	110 lbs 49.9 kg (Safety Factor 10*)
Mesh Material	Galvanized Steel
Package	
Packaging Quantity	1 pcs
Weight, gross	0.101 lb 0.046 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant
CE	Compliant



www.maxdao.com

For more information, please visit: