

Support Grips, Bus Drop, Locking Bale Closed Mesh, Galvanized Steel, Cable Range 0.82-1.00"

- Provide support for flexible cord or bus drop cable at bus duct
- Used for absorb additional strain from vibration, expansion, contraction and flexing
- Locking bale attachment fits around beam or pipe and can be locked in place
- Galvanized steel wire mesh is for indoor use only
- UL&CSA, CE certified



| Classification | |
|------------------------|---|
| Material Number | 6003310 |
| Part Number | - |
| Status | Active |
| Detail Description | Support grips, bus drop, locking bale closed mesh, galvanized steel, cable range 0.82-1.00" |
| Details | |
| Cable Range | 0.82-1.00 in 20.82-25.40 mm |
| Mesh Length | 8.5 in 215.9 mm |
| Bale Length | 16.0 in 406.4 mm |
| Approx. Break Strength | 1900 lbs 861.8 kg |
| Working Load | 190 lbs 86.2 kg (Safety Factor 10*) |
| Mesh Material | Galvanized Steel |
| Package | |
| Packaging Quantity | 1 pcs |
| Weight, gross | 0.159 lb 0.072 kg |
| Certifications | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL&CSA | Compliant |
| CE | Compliant |





www.maxdao.com

For more information, please visit: