

Butterfly Hanger, for 1/2 & 3/8 in cable

- Easy and quick installation
- Robust design & material for outdoor / indoor use
- Fits 3/8 in(M10) hardware kits, banding, round member adapters, angle adapters or standoff kits



Product Classification

| | |
|--------------------|---|
| Material Code | 6001154 |
| Part Number | - |
| Status | Active |
| Detail Description | Butterfly hanger for 1/2 & 3/8 in cable |

General Specifications

| | |
|---------------|---|
| Material Type | Stainless steel 304 |
| Color | Silver |
| Cable Type | Braided coaxial hybrid cable Elliptical waveguide |
| Mounting | 3/8 in (M10) drilled cable ladder |

Dimensions

| | |
|-------------------------------------|--------------------|
| Height | 1.5 in 38.1 mm |
| Width | 1.583 in 40.2 mm |
| Length | 1.583 in 40.2 mm |
| Compatible Cable Jacket OD, maximum | 0.642 in 16.3 mm |
| Compatible Cable Jacket OD, minimum | 0.409 in 10.4 mm |
| Nominal Size | 1/2 & 3/8 in |

Environmental Specifications

| | |
|-------------------------|---|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| UV Resistance | ≥720 hours, base on ISO4892.3-1994 |
| Corrosion Resistance | ≥168 hours in salt spray chamber, base on IEC 60068 -2-11 |
| Vibration Survival Test | ≥6 hours at resonant frequency, base on IEC 60068 -2-6 |

Packaging and Weights

| | |
|----------------------------|---------------------|
| Height, packed | 1.575 in 40 mm |
| Width, packed | 7.874 in 200 mm |
| Length, packed | 7.874 in 200 mm |
| Included | Butterfly hanger |
| Packaging Quantity and UOM | kit of 10 |
| Weight, gross | 0.694 lb 0.315 kg |

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS | Compliant |

