

Butterfly Hanger, for 1-5/8 in cable

- Easy and quick installation
- Robust design & material for outdoor / indoor use
- Fits 3/8 in(M10) hardware kits, banding, round member adapters, angle adapters or standoff kits



Product Classification

Material Code	6001158
Part Number	-
Status	Active
Detail Description	Butterfly hanger for 1-5/8 in cable

General Specifications

Material Type	Stainless steel 304
Color	Silver
Cable Type	Braided coaxial hybrid cable Elliptical waveguide
Mounting	3/8 in (M10) drilled cable ladder

Dimensions

Height	1.5 in 38.1 mm
Width	0.531 in 13.5 mm
Length	6.74 in 171.2 mm
Compatible Cable Jacket OD, maximum	2.047 in 52 mm
Compatible Cable Jacket OD, minimum	1.902 in 48.3 mm
Nominal Size	1-5/8 in

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	≥720 hours,base on ISO4892.3-1994
Corrosion Resistance	≥168 hours in salt spray chamber,base on IEC 60068 -2-11
Vibration Survival Test	≥6 hours at resonant frequency,base on IEC 60068 -2-6

Packaging and Weights

Height, packed	1.575 in 40 mm
Width, packed	7.874 in 200 mm
Length, packed	11.811 in 300 mm
Included	Butterfly hanger
Packaging Quantity and UOM	kit of 10
Weight, gross	1.153 lb 0.523 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

