


Cable Color Clip, for 1/4 in Cable, Green

- Easy and quick installation, no hardware needed
- Robust design & material for outdoor / indoor use
- Eliminates need to identify cables with colored tape



Material Code Part Number - Status Active Detail Description Cable identification clip, for 1/4 in cable, green General Specifications Material Type PC Color Green Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum Nominal Size 1/4 in cable Environmental Specifications Operating Temperature 40 °C to +85 °C (-40 °F to +185 °F) UV Resistance High and Low Temperature Storage Test 272 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test 272 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle 2200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm Length, packed 7.874 in 200 mm	Product Classification	
Status Detail Description General Specifications Material Type PC Color Green Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum Nominal Size I/4 in cable Environmental Specifications Operating Temperature VV Resistance High and Low Temperature Storage Test Retention Force Duty Cycle Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Material Code	6006413
Detail Description General Specifications Material Type PC Color Green Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum Nominal Size 1/4 in cable Environmental Specifications Operating Temperature VY Resistance High and Low Temperature Storage Test Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Part Number	-
General Specifications PC Color Green Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum 0.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Status	Active
Material Type PC Color Green Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum 0.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Detail Description	Cable identification clip, for 1/4 in cable, green
Color Green Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum 0.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	General Specifications	
Dimensions Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum 0.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Material Type	PC
Height 0.787 in 20 mm Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum 0.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Color	Green
Width 0.346 in 8.8 mm Compatible Cable Jacket OD, maximum 0.295 in 7.5 mm Compatible Cable Jacket OD, minimum 0.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Dimensions	
Compatible Cable Jacket OD, maximum O.295 in 7.5 mm O.217 in 5.5 mm Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm 7.874 in 200 mm	Height	0.787 in 20 mm
Compatible Cable Jacket OD, minimum Nominal Size I/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Width	0.346 in 8.8 mm
Nominal Size 1/4 in cable Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Compatible Cable Jacket OD, maximum	0.295 in 7.5 mm
Environmental Specifications Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Compatible Cable Jacket OD, minimum	0.217 in 5.5 mm
Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F) UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Nominal Size	1/4 in cable
UV Resistance ≥1000 hours, base on ISO 4892.3-1994 High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Environmental Specifications	
High and Low Temperature Storage Test ≥72 hours, base on IEC 60068-2-2 Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Retention Force 30-60 N (6.74-13.48 lbf), base on cable Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	UV Resistance	≥1000 hours, base on ISO 4892.3-1994
Duty Cycle ≥200 cycles Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	High and Low Temperature Storage Test	≥72 hours, base on IEC 60068-2-2
Packaging and Weights Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Retention Force	30-60 N (6.74-13.48 lbf), base on cable
Height, packed 0.394 in 10 mm Width, packed 7.874 in 200 mm	Duty Cycle	≥200 cycles
Width, packed 7.874 in 200 mm	Packaging and Weights	
	Height, packed	0.394 in 10 mm
Length, packed 7.874 in 200 mm	Width, packed	7.874 in 200 mm
	Length, packed	7.874 in 200 mm

DOC#ITM04-01, Version:A/2, Updated:02/21/2023



Included Cable identification clip

Packaging Quantity and UOM Kit of 100

Weight, gross 0.212 lb | 0.096 kg

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this

quality management system

ROHS Compliant



www.maxdao.com

For more information, please visit: