

Cat5e cable assembly, with two RJ45 connectors, 500meters

- 4 solid FTP twisted pair
- Meets all Cat5e standards
- Perfect for running in a network
- RoHS certified

**Product Classification**

Material Code	6002804
Part Number	-
Status	Active
Detail Description	Cat5e cable assembly, 4 pair, FTP, 24 AWG solid, black PE jacket, 500meters, with two RJ45 connector

General Specifications

Cable Type	FTP
No. Of Conductor	4 Pair
Conductor Gauge	24 AWG
Conductor Type	Solid
Jacket Material	PE
Jacket Color	Black
Connector Type	RJ45

Dimensions

Conductor Structure	1/0.51 ± 0.008
Insulation Diameter	0.98 mm 0.04 in
Jacket Diameter	6.0 mm 0.24 in
Length	500 Meters

Electrical Specifications

Insulation Resistance	≥ 5000 MΩ, at 20°C
Dielectric Test	1000V DC / 1 min, no breakdown
Rated Voltage	300 V

Environmental Specifications

Operating Temperature	-20 °C to +60 °C
-----------------------	------------------

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 9, 2023
 Public

DATASHEET

Height, packed	310 mm 12.20 in
Width, packed	380 mm 14.96 in
Length, packed	500 mm 19.68 in
Include	Two RJ45 connector
Packaging Quantity and UOM	1 Kit
Weight, gross	17.66 kg 38.93 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

