

Cold Shrink Tube, Gray, $\phi 40 \times 105 \text{mm}$

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification

Material Code	6007382
Part Number	-
Status	Active
Detail description	Cold shrink tube, Gray, $\phi 40 \times 105 \text{mm}$

General Specifications

Material	Silicone rubber
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable size	$\phi 12 \text{mm} - \phi 35 \text{mm}$
Color	Grey
Mastic(Y/N)	N
Shrink ratio	4:1

Dimensions

Length before shrink	105mm 4.13 in
Length after shrink	120mm 4.72 in
Inner diameter before shrink(ID)	40mm 1.57 in
Inner diameter after shrink(ID)	10mm 0.67 in
Thickness after shrink	3mm 0.12 in

Mechanical Specifications

Waterproof resistance	IP67, based on ISO20653:2013
-----------------------	------------------------------

Environmental Specifications

Operating temperature	$-40^{\circ}\text{C} - +85^{\circ}\text{C}$ ($-40^{\circ}\text{F} - +185^{\circ}\text{F}$)
UV resistance	≥ 1000 Hours, based on ISO 4892-3

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 28, 2023

Public

Bag width	260 mm 10.24 in
Bag length	320 mm 12.6 in
Packaging quantity and UOM	1pcs
Weight gross	0.048 kg 0.105 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

