

## Cold Shrink Tube,φ15×80mm

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification		
Material Number	6002887	
Part Number	-	
Status	Active	
Detail description	Cold shrink tube,φ15×80mm	
General Specifications		
Material	Silicone rubber	
Cable type	Corrugated   Elliptical Waveguide   Smoothwall	
Cable size	φ6mm-φ12mm	
Color	Black	
Mastic(Y/N)	Ν	
Shrink ratio	3:1	
Dimensions		
Length before shrink	80 mm   3.15 in	
Length after shrink	110 mm   4.33 in	
Inner diameter before shrink(ID)	15 mm   0.59 in	
Inner diameter after shrink(ID)	5 mm   0.67 in	
Thickness after shrink	2.3 mm   0.20 in	
Environmental Specifications		
Operating temperature	-40℃ to +85℃(-40°Fto +185°F)	
Weatherproof resistance	IP67,based on ISO20653:2013	
UV resistance	≥720Hours,based on ISO 4892-3	
Packaging and Weights		
Bag width	200 mm   7.87 in	
Bag length	320 mm   12.6 in	

For more information, please visit: www.maxdao.com

 $\boxtimes$ 

(in

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Mar 7, 2023 Public Page 1 of 2

DATASHEET



Packaging quantity and UOM	1 pcs
Weight gross	0.0230 kg   0.05 lb
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

For more information, please visit: www.maxdao.com



©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Mar 7, 2023 Public