

Cold Shrink Tube,φ20×200mm

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification

Material Number	6005727
Part Number	-
Status	Active
Detail description	Cold shrink tube,φ20×200mm

General Specifications

Material	Silicone rubber
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable size	φ6mm-φ16mm
Color	Black
Mastic(Y/N)	N
Shrink ratio	4:1

Dimensions

Length before shrink	200 mm 7.87 in
Length after shrink	210 mm 8.27 in
Inner diameter before shrink(ID)	20 mm 0.78 in
Inner diameter after shrink(ID)	5 mm 0.20 in
Thickness after shrink	3 mm 0.12 in

Environmental Specifications

Operating temperature	-40°C to +85°C (-40°F to +185°F)
Weatherproof resistance	IP67,based on ISO20653:2013
UV resistance	≥720Hours,based on ISO 4892-3

Packaging and Weights

Bag width	220 mm 8.66 in
Bag length	320 mm 12.60 in

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised:Mar 6, 2023

Public

Packaging quantity and UOM 1 pcs
Weight gross 0.0432 kg | 0.095 lb

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system
ROHS Compliant

