

Cold Shrink Tube,φ25×175mm

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification

Material Code	6006392
Part Number	-
Status	Active
Detail description	Cold shrink tube,φ25×175mm

General Specifications

Material	Silicone rubber
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable size	φ10mm-φ20mm
Color	Black
Mastic(Y/N)	N
Shrink ratio	4:1

Dimensions

Length before shrink	175mm 5.51 in
Length after shrink	203mm 7.99 in
Inner diameter before shrink(ID)	25mm 0.98 in
Inner diameter after shrink(ID)	7mm 0.28 in
Thickness after shrink	3.2mm 0.13 in

Mechanical Specifications

Waterproof resistance	IP68, based on ISO20653:2013
-----------------------	------------------------------

Environmental Specifications

Operating temperature	-60°C to +95°C (-76°F to +203°F)
UV resistance	≥1000Hours, based on ISO 4892-3

Packaging and Weights

Bag width	220 mm 8.66 in
-----------	------------------

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 27, 2023

Public

Bag length	320 mm 12.60 in
Packaging quantity and UOM	1 pcs
Weight gross	0.054 kg 0.12 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

