

## Cold Shrink Tube, $\phi 35 \times 150 \text{mm}$

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



### Product Classification

Material Number	6005718
Part Number	-
Status	Active
Detail description	Cold shrink tube, $\phi 35 \times 150 \text{mm}$

### General Specifications

Material	Silicone rubber
Cable type	Corrugated   Elliptical Waveguide   Smoothwall
Cable size	$\phi 10 \text{mm} - \phi 30 \text{mm}$
Color	Black
Mastic(Y/N)	N
Shrink ratio	4:1

### Dimensions

Length before shrink	150 mm   5.91 in
Length after shrink	180 mm   7.09 in
Inner diameter before shrink(ID)	35 mm   1.38 in
Inner diameter after shrink(ID)	8 mm   0.32 in
Thickness after shrink	3 mm   0.12 in

### Environmental Specifications

Operating temperature	$-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ ( $-40^{\circ}\text{F}$ to $+185^{\circ}\text{F}$ )
Weatherproof resistance	IP67, based on ISO20653:2013
UV resistance	$\geq 720$ Hours, based on ISO 4892-3

### Packaging and Weights

Bag width	300 mm   11.81 in
Bag length	300 mm   11.81 in

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 6, 2023  
 Public

Packaging quantity and UOM 1 pcs  
Weight gross 0.0668 kg | 0.147 lb

---

**Certifications and Compliance**

---

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system  
ROHS Compliant

