

Cold Shrink Tube, $\phi 44 \times 130$ mm

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification

Material Number	6005728
Part Number	-
Status	Active
Detail description	Cold shrink tube, $\phi 44 \times 130$ mm

General Specifications

Material	Silicone rubber
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable size	$\phi 12$ mm- $\phi 38$ mm
Color	Black
Mastic(Y/N)	N
Shrink ratio	4:1

Dimensions

Length before shrink	130 mm 5.12 in
Length after shrink	160 mm 6.30 in
Inner diameter before shrink(ID)	44 mm 1.73 in
Inner diameter after shrink(ID)	10 mm 0.39 in
Thickness after shrink	3 mm 0.12 in

Environmental Specifications

Operating temperature	-40°C to +85°C (-40°F to +185°F)
Weatherproof resistance	IP67, based on ISO20653:2013
UV resistance	≥720Hours, based on ISO 4892-3

Packaging and Weights

Bag width	300 mm 8.66 in
Bag length	300 mm 11.81 in

Packaging quantity and UOM 1 pcs
Weight gross 0.0688 kg | 0.152 lb

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system
ROHS Compliant

