

Cold Shrink Tube, $\phi 45 \times 80 \text{mm}$

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification

Material Number	6003958
Part Number	-
Status	Active
Detail description	Cold shrink tube, $\phi 45 \times 80 \text{mm}$

General Specifications

Material	Silicone rubber
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable size	$\phi 20 \text{mm} - \phi 40 \text{mm}$
Color	Black
Mastic(Y/N)	N
Shrink ratio	3:1

Dimensions

Length before shrink	80 mm 3.15 in
Length after shrink	110 mm 4.33 in
Inner diameter before shrink(ID)	45 mm 1.77 in
Inner diameter after shrink(ID)	17 mm 0.67 in
Thickness after shrink	2.3 mm 0.09 in

Environmental Specifications

Operating temperature	-40°C to $+85^{\circ}\text{C}$ (-40°F to $+185^{\circ}\text{F}$)
Weatherproof resistance	IP67, based on ISO20653:2013
UV resistance	≥ 720 Hours, based on ISO 4892-3

Packaging and Weights

Bag width	260 mm 10.24 in
Bag length	320 mm 12.6 in
Packaging quantity and UOM	1 pcs

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 8, 2023

Public

Weight gross

0.026 kg | 0.057 lb

Certifications and Compliance

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

ROHS

Compliant

