

## Copper Ferrule Lug , AWG 10#, Single Wire, Nylon-insulated

- Copper Tube Terminals between 0.14mm<sup>2</sup> & 150mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- Insulated ferrules prevent conductor breakage due to bending, wire stress or vibration, while facilitating wire insertions into the terminal block clamp.
- Fraying and breaking of wire strands is prevented and the possibility of an unreliable connection is minimized.
- Colour code meets Indian wire colour standards IS694-2010.




### Product Classification

Material Code	6004511
Detail Description	Copper Ferrule Lug , AWG 10#, Single Wire, Nylon-insulated

### General Specifications

Colour Code	Blue
Terminal Material	Copper
Insulation collar Material	Nylon
Surface	Tin-plated

### Dimensions



Barrel length (B)	0.71 in   18.0 mm
Overall length (L)	1.02 in   26.0 mm
Inner diameter (ID)	0.13 in   3.5 mm
Outer diameter (OD)	0.15 in   3.9 mm
Inner dimensions of the insulating collar (C)	0.27 in   6.9 mm

### Electrical Specifications

Rating - Maximum Voltage	35KV
--------------------------	------

### Environmental Specifications

Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

### Packaging and Weights

Included	Lug
Packaging Quantity and UOM	Kit of 100
Piece Weight	0.088 lb   0.040 kg

---

**Certifications and Certificated**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant

