

Copper Lug, AWG 4/0#, two hole 3/8", hole spacing 1", standard barrel, with inspection window

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars.
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.




Product Classification

| | |
|--------------------|---|
| Material Code | 6005869 |
| Part Number | - |
| Detail Description | Copper Lug, AWG 4/0#, two hole 3/8", hole spacing 1", standard barrel, with inspection window |

General Specifications

| | |
|-------------------|------------------------|
| Colour Code | Purple |
| Material | Copper |
| Tongue Type | Standard |
| Tongue Angle | Straight |
| Surface | Tin-plated |
| Inspection Window | With inspection window |

Dimensions



| | |
|---------------------|-------------------|
| Bolt Size | 3/8 in 10.4 mm |
| Hole Spacing (H) | 1.00 in 25.4 mm |
| Tang Width (C) | 1.02 in 26.5 mm |
| Barrel length (B) | 1.19 in 30.2 mm |
| Overall length (L) | 3.44 in 87.3 mm |
| Inner diameter (ID) | 0.56 in 14.2 mm |
| Outer diameter (OD) | 0.70 in 17.8 mm |

Electrical Specifications

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Mar 07, 2023
Public

Rating - Maximum Voltage 35KV

Environmental Specifications

Operating Temperature -40 °C to +90°C (-40 °F to +212 °F)

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included Lug

Packaging Quantity and UOM 1 pcs

Piece Weight 0.18 lb | 0.08 kg

Certifications and Certificated

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant

UL&CSA Compliant

