

Copper Lug, AWG 12-10#, one hole 10#, Nylon-insulated

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars .
- Copper Terminals between 0.15mm² & 240mm² have bell entry to ensure easy entry even for flexible conductors.
- Internal barrel serrations assure good wire contact and maximum tensile strength.
- Brazed seam protects terminal barrel from splitting during the crimp process.
- "colour code" help choose the right connector.




Product Classification

Material Code	6004274
Detail Description	Copper Lug, AWG 12-10#, one hole 10#, Nylon-insulated

General Specifications

Color Code	Yellow
Material	Copper
Tongue Type	Ring
Surface	Tin-plated

Dimensions



Bolt Size(E)	0.20 in 5.3 mm
Tang Width (W)	0.37 in 9.5 mm
Barrel length (B)	0.51 in 13.0 mm
Overall length (L)	1.00 in 25.5 mm
Inner diameter (d)	0.13 in 3.5 mm
Outer diameter (D)	0.26 in 6.7 mm

Electrical Specifications

Rating - Maximum Voltage	35KV
--------------------------	------

Environmental Specifications

Operating Temperature	-40 °C to +75°C (-40 °F to +167 °F)
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)

Packaging and Weights

Included	Lug
----------	-----

Packaging Quantity and UOM

Kit of 10

Piece Weight

0.06 lb | 0.03 kg

Certifications and Certificated

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

UL&CSA

Compliant

