

Copper Lug, AWG 12-10#, one hole 6#, Non-insulated

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars.
- Copper Terminals between 0.15mm² & 240mm² have bell entry to ensure easy entry even for flexible conductors.
- Internal barrel serrations assure good wire contact and maximum tensile strength.
- Brazed seam protects terminal barrel from splitting during the crimp process.




Product Classification

Material Code	6005219
Detail Description	Copper Lug, AWG 12-10#, one hole 6#, Non-insulated

General Specifications

Material	Copper
Tongue Type	Ring
Tongue Angle	Straight
Surface	Tin-plated

Dimensions



Bolt Size	0.15 in 3.7 mm
Tang Width (C)	0.37 in 9.5 mm
Barrel length (B)	0.27 in 6.8 mm
Overall length (L)	1.06 in 19.8 mm
Inner diameter (ID)	0.13 in 3.5 mm
Outer diameter (OD)	0.22 in 5.6 mm

Electrical Specifications

Rating - Maximum Voltage	600 V
--------------------------	-------

Environmental Specifications

Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included	Lug
Packaging Quantity and UOM	Kit of 10

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 22, 2023
 Public

Piece Weight

0.044 lb | 0.02 kg

Certifications and Certificated

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

UL&CSA

Compliant

