


Copper Lug, AWG 14-10#, one hole 1/4", standard barrel, with inspection window


- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.



Product Classification	
Material Code	6005927
Detail Description	Copper Lug, AWG 14-10# , one hole 1/4", standard barrel, with inspection window
General Specifications	
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Finish	Tin-plated
Inspection Window	With inspection window

Dimensions





Packaging and Weights	
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Environmental Specifications	
Rating - Maximum Voltage	35KV
Electrical Specifications	
Outer diameter (D)	0.22 in 5.5 mm
Inner diameter (d)	0.15 in 3.8 mm
Overall length (L)	1.03 in 26.0 mm
Barrel length (B)	0.39 in 10.0 mm
Tang Width (C)	0.41 in 10.3 mm
Bolt Size	1/4 in 6.4 mm

For more information, please visit: www.maxdao.com



Included



Lug

UL&CSA



Packaging Quantity and UOM Kit of 10 Piece Weight 0.05 lb | 0.02 kg **Certifications and Certificated** Designed, manufactured and/or distributed ISO 9001:2015 under this quality management system RoHS Compliant

Compliant



www.maxdao.com

For more information, please visit: