## **MAXDAO**


## Copper Lug, AWG 6#, one hole 1/4", short barrel, with inspection window


- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm<sup>2</sup> & 800mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.



Product Classification	
Material Code	6005162
Part Number	-
Detail Description	Copper Lug, AWG 6#, one hole 1/4", short barrel, with inspection window
General Specifications	
Material	Copper
Tongue Type	Straight
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	With inspection window

## **Dimensions**





Bolt Size	1/4 in   6.5 mm
Tang Width (C)	0.39 in   10.0 mm
Barrel length (B)	0.53 in   13.5 mm
Overall length (L)	1.44 in   36.5 mm
Inner diameter (ID)	0.22 in   5.6 mm
Outer diameter (OD)	0.31 in   7.9 mm
Electrical Specifications	
Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

For more information, please visit: www.maxdao.com







Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.015 lb   0.007 kg
Certifications and Certificated	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant



For more information, please visit: www.maxdao.com