


Copper Lug, AWG 6#, one hole 3/8",long barrel, without inspection window


- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- The absence without inspection window prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.
- Long barrel provides high pull-out force and increased retention for improved mechanical and electrical performance.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.



Product Classification	
Material Code	6004196
Part Number	-
Detail Description	Copper Lug, AWG 6# ,one hole 3/8",long barrel, without inspection window
General Specifications	
Colour Code	Blue
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	Without inspection window

Dimensions





Bolt Size	3/8 in 10.2 mm
Tang Width (C)	0.60 in 15.5 mm
Barrel length (B)	1.12 in 29.2 mm
Overall length (L)	2.21 in 58.2 mm
Inner diameter (ID)	0.22 in 5.6 mm
Outer diameter (OD)	0.31 in 7.9 mm

Electrical Specifications

DOC#ITM-04-01, Version: A/2, Updated: 02/22/2023



Rating - Maximum Voltage	35KV	
Environmental Specifications		
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)	
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)	
Packaging and Weights		
Included	Lug	
Packaging Quantity and UOM	1 pcs	
Piece Weight	0.024 lb 0.011 kg	
Certifications and Certificated		
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system	
RoHS	Compliant	
UL&CSA	Compliant	