

Copper Lug, AWG6#,two hole 1/4",hole spacing 5/8",short barrel, with inspection window

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.




Product Classification

Material Code	6003102
Part Number	-
Detail Description	Copper Lug, AWG6# ,two holes 1/4",hole spacing 5/8",short barrel,with inspection window

General Specifications

Colour Code	Blue
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	With inspection window

Dimensions



Bolt Size	1/4 in 7.0 mm
Hole Spacing (H)	5/8 in 16.0 mm
Tang Width (C)	0.45 in 12.0 mm
Barrel length (B)	0.45 in 12.0 mm
Overall length (L)	1.95 in 49.0 mm



Inner diameter (ID) 0.22 in | 5.8 mm

Outer diameter (OD) 0.31 in | 7.9 mm

Electrical Specifications

Rating - Maximum Voltage 35KV

Environmental Specifications

Operating Temperature -40 °C to +90°C (-40 °F to +212 °F)

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included Lug

Packaging Quantity and UOM 1 pcs

Weight Per Pcs 0.02 lb | 0.01 kg

Certifications

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant

UL&CSA Compliant