

## Strain Relief Grip, Deluxe Cord, NPT 1-1/4", Straight Male, Cable Range 0.875-1.00"

- For indoor and outdoor where cables or wires are • exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL&CSA**, CE certified •

| <ul> <li>For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.</li> <li>Prevents severe cord bending and pull-out.</li> <li>Helps eliminate direct tension from terminals and remove strain from critical electrical connection</li> <li>Multi-weave provides easy cable installation</li> <li>UL&amp;CSA, CE certified</li> </ul> |   |
|---|---|
| Classification  |   |
| Material Code   | 6003271   |
| Part Number   | -   |
| Status  | Active  |
| Detail Description  | Strain relief grip, deluxe cord, NPT 1-1/4", straight male,<br>cable range 0.875-1.00"                          |
| Details   |   |
| Cable Range   | 0.875-1.00 in   22.23 -25.40 mm   |
| Thread Size   | NPT 1-1/4"  |
| Mesh Length   | 8.0 in   203.2 mm   |
| Mesh Material   | Stainless Steel   |
| Body Material   | Aluminum  |
| Performance   |   |
| Flammability  | UL 94HB & UL 94V-2  |
| Hazardous Locations   | Suitable for use in hazardous locations per Class I, Div. 2;<br>Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures  | -34 °C to +115 °C (-30 °F to +240 °F)   |
| Wet Locations   | Suitable for use in wet locations when used with a listed sealing ring between box and fitting                  |
| Package   |   |
| Packaging Quantity  | 1 pcs   |
| Weight, gross   | 0.485 lb   0.22 kg  |
| Certifications  |   |

ISO 9001:2015

RoHS

Designed, manufactured and/or distributed under this quality management system

Compliant

For more information, please visit: www.maxdao.com

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 23, 2023 Public

Page 1 of 2



DATASHEET

UL&CSA

CE

Compliant

Compliant

## MAXDAO

For more information, please visit: www.maxdao.com

 $\square$ ſ'n

©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 23, 2023 Public

