

Strain Relief Grip, Deluxe Cord, NPT 1/2", Straight Male, Cable Range 0.500-0.625"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL&CSA, CE certified



Classification		
Material Code		6002921
Part Number		-
Status		Active
Detail Description		Strain relief grip, deluxe cord, NPT 1/2", straight male, cable range 0.500-0.625"
Details		
Cable Range		0.500-0.625 in 12.7-15.9 mm
Thread Size		NPT 1/2"
Mesh Length		6.5 in 165.1 mm
Mesh Material		Stainless Steel
Body Material		Aluminum
Performance		
Flammability		UL 94HB & UL 94V-2
Hazardous Locations		Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures		-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations		Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package		
Packaging Quantity		1 pcs
Weight, gross		0.096 lb 0.044 kg
Certifications		
ISO 9001:2015		Designed, manufactured and/or distributed under this quality management system
RoHS		Compliant
UL&CSA		Compliant
For more information, please visit: www.maxdao.com	©Copyright 2023 Maxdao Inc. All rights re The information contained herein is subject changes or modify the contents of this docu Paviced: Eab 20.2013	to change without notice. We reserve the right to make technical

fin 🖂

Revised: Feb 20, 2023

Public

DATASHEET

CE

Compliant



Page 2 of 2

For more information, please visit: www.maxdao.com

in

©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 20, 2023 Public

 \square