

Strain Relief Grip, Deluxe Cord, NPT 2-1/2", Straight Male, Cable Range 2.187-2.312"

- For indoor and outdoor where cables or wires are • exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out. •
- Helps eliminate direct tension from terminals and • remove strain from critical electrical connection
- Multi-weave provides easy cable installation •
- UL&CSA, CE certified



| Classification | |
|---|---|
| Material Code | 6003488 |
| Part Number | - |
| Status | Active |
| Detail Description | Strain relief grip, deluxe cord, NPT 2-1/2", straight male, cable range 2.187-2.312" |
| Details | |
| Cable Range | 2.187-2.312 in 55.55 -58.72 mm |
| Thread Size | NPT 2-1/2" |
| Mesh Length | 17.0 in 431.8 mm |
| Mesh Material | Stainless Steel |
| Body Material | Aluminum |
| Performance | |
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2 Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |
| Package | |
| Packaging Quantity | 1 pcs |
| Weight, gross | 2.068 lb 0.938 kg |
| Certifications | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL&CSA | Compliant |
| CE | Compliant |
| For more information, please visit: www.maxdao.com | ©Copyright 2023 Maxdao Inc. All rights reserved. Page 1 of 1 The information contained herein is subject to change without notice. We reserve the right to make technical |

Public

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 27, 2023

