

## Strain Relief Grip, Deluxe Cord, NPT 2", Straight Male, Cable Range 1.687-1.812"

- For indoor and outdoor where cables or wires are • exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out. •
- Helps eliminate direct tension from terminals and • remove strain from critical electrical connection
- Multi-weave provides easy cable installation •
- UL&CSA, CE certified .

| Classification         |   |
|------------------------|---|
| Material Code          | 6003339   |
| Part Number            | <u>-</u>  |
| Status                 | Active  |
| Detail Description     | Strain relief grip, deluxe cord, NPT 2", straight male, cable<br>range 1.687-1.812"                             |
| Details                |   |
| Cable Range            | 1.687-1.812 in   42.85 -46.02 mm  |
| Thread Size            | NPT 2"  |
| Mesh Length            | 15.5 in   393.7 mm  |
| Mesh Material          | Stainless Steel   |
| Body Material          | Aluminum  |
| Performance            |   |
| Flammability           | UL 94HB & UL 94V-2  |
| Hazardous Locations    | Suitable for use in hazardous locations per Class I, Div. 2;<br>Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F)   |
| Wet Locations          | Suitable for use in wet locations when used with a listed sealing ring between box and fitting                  |
| Package                |   |
| Packaging Quantity     | 1 pcs   |
| Weight, gross          | 0.937 lb   0.425 kg   |
| Certifications         |   |
| ISO 9001:2015          | Designed, manufactured and/or distributed under this quality management system                                  |
|                        | Compliant   |



www.maxdao.com

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 25, 2023 Public

DATASHEET

UL&CSA

CE

Compliant

Compliant

## MAXDAO

For more information, please visit: www.maxdao.com

 $\square$ ſ'n

©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 25, 2023 Public

