

Strain Relief Grip, Deluxe Cord, NPT 2", Straight Male, Cable Range 2.062-2.187"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL&CSA, CE certified

**Classification**

Material Code	6003484
Part Number	-
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 2", straight male, cable range 2.062-2.187"

Details

Cable Range	2.062-2.187 in 53.37 -55.55 mm
Thread Size	NPT 2"
Mesh Length	17.0 in 431.8 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Package

Packaging Quantity	1 pcs
Weight, gross	1.993 lb 0.904 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

DATASHEET

MAXDAO

UL&CSA

Compliant

CE

Compliant

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 25, 2023

Public

Page 2 of 2

DOC#ITM04-01, Version:A/2, Updated:02/25/2023