

**Strain Relief Grip, Deluxe Cord, NPT 3/4", 90°Male, Cable Range 0.250-0.375"**

- For use in indoor & outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture and coolants.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL&CSA, CE certified

**Classification**

Material Code	6004409
Part Number	-
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3/4", 90° male, cable range 0.250-0.375"

**Details**

Cable Range	0.250-0.375 in   6.35-9.53 mm
Thread Size	NPT 3/4"
Mesh Length	4.25 in   108.0 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

**Performance**

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

**Package**

Packaging Quantity	1 pcs
Weight, gross	0.194 lb   0.088 kg

**Certifications**

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

DATASHEET

RoHS	Compliant
UL&CSA	Compliant
CE	Compliant

