

Strain Relief Grip, Deluxe Cord, NPT 3/4", 90°Male, Cable Range 0.500-0.625"

- For use in indoor & outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture and coolants.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL&CSA, CE certified



Classification

| | |
|--------------------|---|
| Material Code | 6004360 |
| Part Number | - |
| Status | Active |
| Detail Description | Strain relief grip, deluxe cord, NPT 3/4", 90° male, cable range 0.500-0.625" |

Details

| | |
|---------------|---------------------------------|
| Cable Range | 0.500-0.625 in 12.70-15.88 mm |
| Thread Size | NPT 3/4" |
| Mesh Length | 6.0 in 152.4 mm |
| Mesh Material | Stainless Steel |
| Body Material | Aluminum |

Performance

| | |
|------------------------|--|
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |

Package

| | |
|--------------------|---------------------|
| Packaging Quantity | 1 pcs |
| Weight, gross | 0.202 lb 0.092 kg |

Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

DATASHEET

UL&CSA

Compliant

CE

Compliant

For more information, please visit:

www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 23, 2023

Public