## DOC#ITM04-01, Version:A/2, Updated:02/21/2023



## Strain Relief Grip, Deluxe Cord, NPT 3/4", Straight Male, Cable Range 0.625-0.750"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL&CSA, CE certified



Classification	
Material Code	6003051
Part Number	-
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3/4", straight male, cable range 0.625-0.750"
Details	
Cable Range	0.625-0.750 in   15.88-19.05 mm
Thread Size	NPT 3/4"
Mesh Length	8.0 in   203.2 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	0.150 lb   0.068 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant

For more information, please visit: www.maxdao.com





CE Compliant

