

Strain Relief Grip, Deluxe Cord, NPT 3/8", Straight Male, Cable Range 0.187-0.250"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection

Revised: Feb 20, 2023

Public

fin

- Multi-weave provides easy cable installation
- UL&CSA, CE certified



Classification		
Material Code		6004449
Part Number		-
Status		Active
Detail Description		Strain relief grip, deluxe cord, NPT 3/8", straight male, cable range 0.187-0.250"
Details		
Cable Range		0.187-0.250 in 4.75-6.35 mm
Thread Size		NPT 3/8"
Mesh Length		2.25 in 57.2 mm
Mesh Material		Stainless Steel
Body Material		Aluminum
Performance		
Flammability		UL 94HB & UL 94V-2
Hazardous Locations		Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures		-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations		Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package		
Packaging Quantity		1 pcs
Weight, gross		0.057 lb 0.026 kg
Certifications		
ISO 9001:2015		Designed, manufactured and/or distributed under this quality management system
RoHS		Compliant
UL&CSA		Compliant
For more information, please visit: www.maxdao.com	©Copyright 2023 Maxdao Inc. All rights ree The information contained herein is subject to changes or modify the contents of this docur Boyicrof Exp 20, 2023	to change without notice. We reserve the right to make technical

DATASHEET

CE

Compliant



Page 2 of 2

For more information, please visit: www.maxdao.com

in

©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 20, 2023 Public

 \square